



NOTES. FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 3. PHOSPHOR BRONZE PER QQ-B-750
 4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 5. JIS H 3260, C 3501

1. CRIMPED FERRULE
 HEX CRIMP SIZE .178"
 2. CRIMPED CONTACT PIN
 HEX CRIMP SIZE .068"

DIMENSIONS ARE IN MILLIMETERS

UNLESS OTHERWISE SPECIFIED TOLERANCES			
0.5-6	= ±0.2		
6-30	= ±0.4		
30-120	= ±0.6		
120-315	= ±1		
315-1000	= ±1.6		
1000-2000	= ±2.4		

6	FERRULE	NOTE 5	NOTE 2	1	FR-52/44-38/3 X14	PART NO. B6121E1-ND3G-5-50			
5	SLEEVE	DELTRIN	NATURAL	1	SL-25/17X115	APPROVED DATE 10-11-01'			
4	CONTACT PIN	NOTE 3	NOTE 4	1	B74000-8-25/06	CHECKED DATE 10-11-01'			
3	INSULATOR	DELTRIN	NATURAL	1	B74050-3-50-B	DRAWN DATE 10-11-01'			
2	BODY	NOTE 1	NOTE 2	1	B74000-2	FILE NO.			
1	HOUSING	NOTE 1	NOTE 2	1	B70002-1-38/27				
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	3/1	ISSUE	A

Amphenol	
TITLE BNC CRIMP JACK (FOR RG-174/U,188A/U,316/U)	
DRAWING NO. KJ-B6121E1-ND3G-316U-50	
ITEM NO.	