



RECOMMENDED MOUNTING HOLE

12.7 HEX
2.3

1. MAX. PANEL THICKNESS=3.2mm

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. PHOSPHOR BRONZE PER QQ-B-750
 5. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE

DIMENSIONS ARE IN MILLIMETERS				PART NO.	
UNLESS OTHERWISE SPECIFIED TOLERANCES				B6351B1-ND3G-50	
0.5-6 = ±0.2				APPROVED	DATE
6-30 = ±0.4					10-11-01'
30-120 = ±0.6				CHECKED	DATE
120-315 = ±1					10-11-01'
315-1000 = ±1.6				DRAWN	DATE
1000-2000 = ±2.4					10-11-01'
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	FILE NO.

<h1>Amphenol</h1>			
		TITLE	BNC BULKHEAD RECEPT. JACK
		DRAWING NO.	KJ-B6351B1-ND3G-50
		ITEM NO.	

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
6	SOLDER TAG			1	B7310-7
5	HEX NUT			1	HN127-3/8-32 X23
4	LOCK WASHER			1	LW-127/97X05
3	CONTACT PIN			1	B7310-3-50
2	INSULATOR	DELTRIN	NATURAL	1	B7310-2-50-C
1	BODY			1	B7310-1