



REVISIONS		
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER QQ-B-626
2. BRASS PER QQ-B-613
3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
4. PHOSPHOR BRONZE PER QQ-B-750
5. NICKEL PL. 200 MIN THICK OVER COPPER STRIKE
6. NICKEL PL. 100 MIN. THICK OVER COPPER PL. 300 MIN. THICK OVER COPPER STRIKE
7. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
8. ZINC DIECAST

12	LOCK RING	NOTE 1	NOTE 3	1	LR-79/62X08
11	CONTACT PIN	NOTE 1	NOTE 7	1	B9073D1-11-B
10	WASHER	NOTE 2	NOTE 3	1	WS-128/9X08
9	SPRING	SK5	NOTE 5	2	B50000-6
8	RETAINER RING	NOTE 1	NOTE 3	1	B50000-5
7	GASKET	RUBBER	RED	1	GS-115/8X15
6	INSULATOR	DELTRIN	NATURAL	1	B9073D1-6-50-B
5	BODY	NOTE 1	NOTE 3	1	B9073D1-5
4	CONTACT PIN	NOTE 4	NOTE 7	1	B9073D1-4-A
3	INSULATOR	DELTRIN	NATURAL	2	B9073D1-3-50-A
2	HOUSING	NOTE 8	NOTE 6	1	B9073D1-2
1	SHELL	NOTE 8	NOTE 6	1	B500002-1
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS
 UNLESS OTHERWISE SPECIFIED TOLERANCES
 0.5-6 = ±0.2
 6-30 = ±0.4
 30-120 = ±0.6
 120-315 = ±1
 315-1000 = ±1.6
 1000-2000 = ±2.4

PART NO.	B9073D1-ND3G-50	
APPROVED	DATE	10-11-01'
CHECKED	DATE	10-11-01'
DRAWN	DATE	10-11-01'
FILE NO.		

Amphenol

TITLE
BNC "T" ADAPTOR JACK-PLUG-JACK

DRAWING NO.
KJ-B9073D1-ND3G-50

ITEM NO.