



- 1. CRIMPED FERRULE
HEX CRIMP SIZE .128"
- 2. CONTACT PIN TO SOLDER

Amphenol

TITLE MCX R/A CRIMP PLUG
(FOR RG-174/U, 188A/U, 316/U)

DRAWING NO. KJ-MCX1112A1-3GT30G-316U-50

ITEM NO.

PART NO.	MCX1112A1-3GT30G-5-50
APPROVED	DATE 10-11-01'
CHECKED	DATE 10-11-01'
DRAWN	DATE 10-11-01'

- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. GOLD PL. 30 MIN. THICK OVER COPPER PL. 100 MIN. THICK
 5. TEFLON MIL-P-19468
 6. BERYLLIUM COPPER PER QQ-C-530

NO.	DESCRIPTION	MATERIAL	FINISH	QTY	DRAWING NO.	SCALE	6/1	ISSUE	A	FILE NO.
7	FERRULE	COPPER	NOTE 3	1	FR-38/3X7C					
6	COVER	NOTE 2	NOTE 3	1	CV-405X08-T					
5	INSULATOR	DELRIN	NATURAL	1	MCX1112A1-5					
4	CONTACT PIN	NOTE 1	NOTE 4	1	MCX1112A1-4					
3	INSULATOR	NOTE 5	NATURAL	1	MCX1112A1-3T-50-C					
2	BDDY	NOTE 6	NOTE 3	1	MCX1112A1-2-D					
1	HOUSING	NOTE 1	NOTE 3	1	MCX1112A1-1-23/17-D					

REVISIONS	
ISS	DESCRIPTION\PER REQUEST\DATE