



1. CRIMPED FERRULE
HEX CRIMP SIZE .128"
2. CONTACT PIN TO SOLDER

- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. BERYLLIUM COPPER PER QQ-C-530
 5. GOLD PL. 30 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 6. TEFLON MIL-P-19468

6 FERRULE		COPPER	NOTE 3	1	FR-38/3X7C	PART NO. MMCX1112A1-3GT30G-5-50		Amphenol	
5 COVER		NOTE 2	NOTE 3	1	CV-29X05-T	APPROVED		TITLE MMCX R/A CRIMP PLUG (FOR RG-174/U,188A/U,316/U)	
4 RETAINER RING		NOTE 4	NOTE 3	1	MMCX1121A1-5-C	DATE 10-11-01		DRAWING NO. KJ-MMCX1112A1-3GT30G-316U-50	
3 CONTACT PIN		NOTE 1	NOTE 5	1	MMCX1112A1-4-B	CHECKED		ITEM NO.	
2 INSULATOR		NOTE 6	NATURAL	1	MMCX1112A1-3T-50-B	DRAWN			
1 HOUSING WITH BODY		NOTE 1	NOTE 3	1	MMCX1112A1-1S-23/17-B	DATE 10-11-01			
NO. DESCRIPTION		MATERIAL	FINISH	QTY	DRAWING NO.	SCALE	6/1	ISSUE	A
1			2	3	4	FILE NO.		6 7 8	

Amphenol

TITLE MMCX R/A CRIMP PLUG
(FOR RG-174/U,188A/U,316/U)

DRAWING NO. KJ-MMCX1112A1-3GT30G-316U-50

ITEM NO.

PART NO. MMCX1112A1-3GT30G-5-50

APPROVED DATE 10-11-01

CHECKED DATE 10-11-01

DRAWN DATE 10-11-01

FILE NO.

SCALE 6/1 ISSUE A

DIMENSIONS ARE IN MILLIMETERS

UNLESS OTHERWISE SPECIFIED

TOLERANCES

0.5-6 = ±0.2

6-30 = ±0.4

30-120 = ±0.6

120-315 = ±1

315-1000 = ±1.6

1000-2000 = ±2.4