



- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
  2. BRASS PER QQ-B-613
  3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
  4. PHOSPHOR BRONZE PER QQ-B-750
  5. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
  6. TEFLON MIL-P-19468

1. CRIMPED CONTACT PIN  
HEX CRIMP SIZE .100"

8	CONTACT PIN	NOTE 4	NOTE 5	1	N7000-4-3/26
7	NUT	NOTE 1	NOTE 3	1	B5201-12-19/111
6	WASHER	NOTE 2	NOTE 3	1	WS-16/115X05
5	GASKET	SILICONE	RED	1	B5201-10
4	BRAID CLAMP	NOTE 1	NOTE 3	1	B5201-9-111/91
3	WASHER	NOTE 2	NOTE 3	1	WS-145/75X05
2	INSULATOR	NOTE 6	NATURAL	1	N5000-4T-50-A
1	BODY	NOTE 1	NOTE 3	1	N7201-1-19/101
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS  
UNLESS OTHERWISE SPECIFIED TOLERANCES

0.5-6	= ±0.2
6-30	= ±0.4
30-120	= ±0.6
120-315	= ±1
315-1000	= ±1.6
1000-2000	= ±2.4

PART NO.	N6141A2-NT3G-7A-50
APPROVED	DATE 10-11-01'
CHECKED	DATE 10-11-01'
DRAWN	DATE 10-11-01'
SCALE	2.5/1
ISSUE	A
FILE NO	

<b>Amphenol</b>	
TITLE N CLAMP JACK (FOR RG-213/U,214/U,8/U)	
DRAWING NO. KJ-N6141A2-NT3G-214U-50	
ITEM NO.	