

1	2		3	4	5	6	7	8		
REVISIONS										
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE								
<p>RECOMMENDED CABLE STRIPPING DIM'S</p>										
<p>NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)</p> <p>1. BRASS PER QQ-B-626</p> <p>2. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE</p> <p>3. GOLD PL. 30 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE</p> <p>4. TEFLON MIL-P-19468</p>										
<p>1. CRIMPED FERRULE HEX CRIMP SIZE .128"</p> <p>2. CRIMPED CONTACT PIN SQ. CRIMP SIZE 0.7(mm)</p>										
7	HEAT SHRINK TUBING			1	HT-56/5X193	<p>DIMENSIONS ARE IN MILLIMETERS</p> <p>UNLESS OTHERWISE SPECIFIED TOLERANCES</p> <p>0.5-6 = ±0.2</p> <p>6-30 = ±0.4</p> <p>30-120 = ±0.6</p> <p>120-315 = ±1</p> <p>315-1000 = ±1.6</p> <p>1000-2000 = ±2.4</p>			<p>PART NO. SMB1121A1-3GT30G-5-50</p> <p>APPROVED DATE 10-11-01'</p> <p>CHECKED DATE 10-11-01'</p> <p>DRAWN DATE 10-11-01'</p>	
6	FERRULE	COPPER	NOTE 2	1	FR-38/3X7C	<p>Amphenol</p> <p>TITLE SMB CRIMP JACK (FOR RG-174/U,188A/U,316/U)</p>				
5	CONTACT PIN	NOTE 1	NOTE 3	1	SMB1121A1-5-096/06	<p>DRAWING NO. KJ-SMB1121A1-3GT30G-316U-50</p>				
4	BARREL	NOTE 1	NOTE 2	1	SMB6121A1-4-23/17-C	<p>ITEM NO.</p>				
3	INSULATOR	NOTE 4	NATURAL	1	SMB6121B2-3T-50					
2	INSULATOR	NOTE 4	NATURAL	1	SMB1121A1-2T-50					
1	BODY	NOTE 1	NOTE 2	1	SMB1121A1-1-B					
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	4/1	ISSUE	A	FILE NO.

F

F

E

E

D

D

C

C

B

B

A

A

1 2 3 4 5 6 7 8